

Exam : Microsoft 70-504

**Title : TS: Microsoft .NET
Framework 3.5 -C Windows
Workflow Foundation**

Version : Demo



Top 3 Customers in Test4pass - Best IT certifications Team



Abbigail, who is proficient in Microsoft technology. After read our Study guides of Microsoft , She think test4pass is the best for IT candidates.

is the best for IT candidates.



Ramsden, who was majored in Manager IT technologys. He has many years of education experience. With his help, many of his candidates have won the certificate. he said:

test4pass' materials are the real one!



The IT experts of American company are training with test4pass braindumps, the manager of the company said: that will help them a lot

by using test4pass.

HOT Certifications On Test4pass

Cisco Certifications

[CCNA](#) [CCDA](#) [CCNP](#) [CCDP](#) [CCVP](#) [CCSP](#) [CCIP](#) [CCIE](#) [CCDE](#) [Data Center](#) [Sales Expert](#)

Microsoft Certifications

[MCP](#) [MCSE](#) [MCITP](#) [MCTS](#) [MCSE2003](#) [MCPD](#) [MCSA.NET](#) [MCDST](#) [TS](#) [Exchange Server2007](#)
[MCSE2003 Security](#) [MCSE2003 Messaging](#) [Microsoft Business Solutions](#)

IBM Certifications

[Certified Administrator](#) [Certified Systems Expert](#) [Solutions Expert](#) [System Administrator](#)
[DB2](#) [Certified Advanced Technical Expert](#) [Certified Advanced System Administrator](#)
[Lotus Certification](#) [WebSphere](#) [Cognos 8 BI](#) [Certified Associate Developer](#) [Tivoli Software](#)

CompTIA Certifications

[A+](#) [CDIA+](#) [CTT+](#) [e-Biz+](#) [CompTIA HTI+](#) [i-NET+](#) [Linux+](#) [Network+](#) [Project+](#) [RFID+](#) [Security+](#)
[Server+](#) [PDI+](#) [Convergence+](#)

1. You are writing a sequential console workflow that consists of a delay activity and a code activity, as shown in the exhibit. (Click the Exhibit button for the sequential console workflow image)

In the execution code of the second activity, you try to modify the workflow as follows:

```
private void codeActivity_ExecuteCode(object sender, EventArgs e)
{
    CodeActivity delay = sender as CodeActivity;
    Console.WriteLine(delay.Name);
    WorkflowChanges workflowChanges = new WorkflowChanges(this);
    CodeActivity codeActivity = new CodeActivity();
    codeActivity.Name = "codeActivity2";
    codeActivity.ExecuteCode += new EventHandler(codeActivity2_ExecuteCode);
    workflowChanges.TransientWorkflow.Activities.Add(codeActivity);
    this.ApplyWorkflowChanges(workflowChanges);
}

private void codeActivity2_ExecuteCode(object sender, EventArgs e)
{
    CodeActivity codeActivity = sender as CodeActivity;
    Console.WriteLine(codeActivity.Name);
    Console.ReadLine();
}
```

You also have set the modifiability of the workflow to a code condition that is set to the following function:

```
private void UpdateCondition(object sender, ConditionalEventArgs e)
{
    if (TimeSpan.Compare(this.delayActivity.TimeoutDuration, new TimeSpan(0, 0, 5)) > 0) {
        e.Result = false;
    }
    else {
        e.Result = true;
    }
}
```

Which code segment should you use to handle the exception?

A. workflowChanges.TransientWorkflow.Activities.Add(codeActivity);

```
try {
    this.ApplyWorkflowChanges(workflowChanges);
}
```

```
catch (ArgumentOutOfRangeException ex) {
    Console.WriteLine(ex.GetType().ToString());
    Console.ReadLine();
}
B. workflowChanges.TransientWorkflow.Activities.Add(codeActivity);
try {
    this.ApplyWorkflowChanges(workflowChanges);
}
catch (InvalidProgramException ex) {
    Console.WriteLine(ex.GetType().ToString());
    Console.ReadLine();
}
C. workflowChanges.TransientWorkflow.Activities.Add(codeActivity);
try {
    this.ApplyWorkflowChanges(workflowChanges);
}
catch (InvalidOperationException ex) {
    Console.WriteLine(ex.GetType().ToString());
    Console.ReadLine();
}
D. workflowChanges.TransientWorkflow.Activities.Add(codeActivity);
try {
    this.ApplyWorkflowChanges(workflowChanges);
}
catch (OverflowException ex) {
    Console.WriteLine(ex.GetType().ToString());
    Console.ReadLine();
}
```

Answer: C

2. Question

You are writing a sequential console workflow that consists of a delay activity and a code activity, as shown in the exhibit. (Click the Exhibit button for the sequential console workflow image.)

In the execution code of the second activity, you try to modify the workflow as follows:

```
Private Sub delayActivity_InitializeTimeoutDuration(ByVal sender As System.Object, ByVal e As System.EventArgs)
```

```
Console.Title = "Modifiability of a Workflow"
Console.WriteLine("Wait ...")
End Sub

Private Sub codeActivity_ExecuteCode(ByVal sender As System.Object, ByVal e As System.EventArgs)
Dim delay As DelayActivity = CType(sender, DelayActivity)
Console.WriteLine(delay.Name)
Dim workflowChanges As New WorkflowChanges(Me)
Dim codeActivity As New CodeActivity()
codeActivity.Name = "codeActivity2"
AddHandler codeActivity.ExecuteCode, AddressOf Me.codeActivity2_ExecuteCode
workflowChanges.TransientWorkflow.Activities.Add(codeActivity)
Me.ApplyWorkflowChanges(workflowChanges)
End Sub

Private Sub codeActivity2_ExecuteCode(ByVal sender As System.Object, ByVal e As System.EventArgs)
Dim codeActivity As CodeActivity = CType(sender, CodeActivity)
Console.WriteLine(codeActivity.Name)
Console.ReadLine()
End Sub
```

You also have set the modifiability of the workflow to a code condition that is set to the following function:

```
Private Sub UpdateCondition(ByVal sender As System.Object, ByVal e As ConditionalEventArgs)
If (TimeSpan.Compare(Me.delayActivity.TimeoutDuration, New TimeSpan(0, 0, 5)) > 0) Then
e.Result = False
Else
e.Result = True
End If
End Sub
```

Which code segment should you use to handle the exception?

A. workflowChanges.TransientWorkflow.Activities.Add(codeActivity)

Try

Me.ApplyWorkflowChanges(workflowChanges)

Catch ex As ArgumentOutOfRangeException

Console.WriteLine(ex.GetType().ToString())

Console.ReadLine()

End Try

B. workflowChanges.TransientWorkflow.Activities.Add(codeActivity)

```
Try
Me.ApplyWorkflowChanges(workflowChanges)
Catch ex As InvalidProgramException
Console.WriteLine(ex.GetType().ToString())
Console.ReadLine()
End Try
C. workflowChanges.TransientWorkflow.Activities.Add(codeActivity)
Try
Me.ApplyWorkflowChanges(workflowChanges)
Catch ex As InvalidOperationException
Console.WriteLine(ex.GetType().ToString())
Console.ReadLine()
End Try
D. workflowChanges.TransientWorkflow.Activities.Add(codeActivity)
Try
Me.ApplyWorkflowChanges(workflowChanges)
Catch ex As OverflowException
Console.WriteLine(ex.GetType().ToString())
Console.ReadLine()
End Try
```

Answer: C

3. Question

A custom activity defined in an assembly named LitwareActivities is defined as follows:

```
namespace LitwareActivities
{
public class WriteLineActivity : Activity
{
protected override ActivityExecutionStatus Execute(ActivityExecutionContext executionContext)
{
Console.WriteLine(Message);
return ActivityExecutionStatus.Closed;
}
private string _message;
public string Message
{
```

```
get { return _message; }
set { _message = value; }
}
...
}
}
```

You need to create a sequential workflow where the execution path can be generated on the fly by an application.

Which XML code segment should you use?

A. <SequentialWorkflowActivity

```
xmlns="http://schemas.microsoft.com/winfx/2006/xaml/workflow"
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
xmlns:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">
<Litware:WriteLineActivity Message="Hello, WF"/>
</SequentialWorkflowActivity>
```

B. <Workflow

```
xmlns="http://schemas.microsoft.com/winfx/2006/xaml/workflow"
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
xmlns:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">
<Litware:WriteLineActivity Message="Hello, WF"/>
</Workflow>
```

C. <Workflow

```
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
class:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">
<Litware:WriteLineActivity Message="Hello, WF"/>
</Workflow>
```

D. <SequentialWorkflowActivity

```
class:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">
<Litware:WriteLineActivity Message="Hello, WF"/>
</SequentialWorkflowActivity>
```

Answer: A

4. Question

A custom activity defined in an assembly named LitwareActivities is defined as follows:

Namespace LitwareActivities

Public Class WriteLineActivity

```

Inherits Activity
Protected Overrides Function Execute(ByVal executionContext As
System.Workflow.ComponentModel.ActivityExecutionContext) As
System.Workflow.ComponentModel.ActivityExecutionStatus
Console.WriteLine(Message)
Return ActivityExecutionStatus.Closed
End Function
Private aMessage As String
Public Property Message() As String
Get
Return aMessage
End Get
Set(ByVal value As String)
aMessage = value
End Set
End Property
End Class
End Namespace

```

You need to create a sequential workflow where the execution path can be generated on the fly by an application.

Which XML code segment should you use?

A. <SequentialWorkflowActivity

```

xmlns="http://schemas.microsoft.com/winfx/2006/xaml/workflow"
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
xmlns:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">
<Litware:WriteLineActivity Message="Hello, WF"/>
</SequentialWorkflowActivity>

```

B. <Workflow

```

xmlns="http://schemas.microsoft.com/winfx/2006/xaml/workflow"
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
xmlns:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">
<Litware:WriteLineActivity Message="Hello, WF"/>
</Workflow>

```

C. <Workflow

```

xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"

```

```
class:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">  
<Litware:WriteLineActivity Message="Hello, WF"/>  
</Workflow>
```

D. <SequentialWorkflowActivity

```
class:Litware="clr-namespace:LitwareActivities;assembly=LitwareActivities">  
<Litware:WriteLineActivity Message="Hello, WF"/>  
</SequentialWorkflowActivity>
```

Answer: A

5. Question

You create an application in which users design simple sequential workflows. The designs are stored as XOML in a SQL database. You need to start one of these sequential workflows from within your own workflow.

What should you do?

- A. Include a custom activity with a code segment that includes an invocation to the CreateWorkflow method of the WorkflowRuntime class and then starts the workflow. The signature of the CreateWorkflow method invoked uses only the workflowType parameter.
- B. Include a custom activity with a code segment that includes an invocation to the CreateWorkflow method of WorkflowRuntime class and then starts the workflow. The signature of the CreateWorkflow method invoked uses only the XmlReader and workflowDefinitionReader parameters.
- C. Include a custom activity with a code segment that includes an invocation to the CreateWorkflow method of the WorkflowRuntime class and then starts the workflow. The signature of the CreateWorkflow method invoked uses only the workflowType, Dictionary<string,Object> namedArgumentValues, and Guid instanceId parameters.
- D. Include and configure an InvokeWorkflow activity

Answer: B

6. Question

You create an application in which users design simple sequential workflows. The designs are stored as XOML in a SQL database. You need to start one of these sequential workflows from within your own workflow.

What should you do?

- A. Include a custom activity with a code segment that includes an invocation to the CreateWorkflow method of the WorkflowRuntime class and then starts the workflow. The signature of the CreateWorkflow method invoked uses only the workflowType parameter.
- B. Include a custom activity with a code segment that includes an invocation to the CreateWorkflow method of WorkflowRuntime class and then starts the workflow. The signature of the CreateWorkflow method

invoked uses only the XmlReader and workflowDefinitionReader parameters.

C. Include a custom activity with a code segment that includes an invocation to the CreateWorkflow method of the WorkflowRuntime class and then starts the workflow. The signature of the CreateWorkflow method invoked uses only the workflowType, Dictionary<string, Object> namedArgumentValues, and Guid instanceId parameters.

D. Include and configure an InvokeWorkflow activity

Answer: B

7. Question

You use a built-in tracking service to track specific workflow parameters.

You need to check whether the workflow parameters have been stored in the tracking database.

What should you do? (Each correct answer presents part of a solution. Choose two.)

A. Display the contents of the WorkflowInstance table of the tracking database.

B. Include the SqlTrackingQuery class in a code segment to retrieve tracked workflows and SqlTrackingWorkflowInstance class to inspect them.

C. Use the ActivityTrackingLocation class to determine if the value has been set to a database.

D. Display the contents of the TrackingDataItem table of the tracking database.

Answer: B AND D

8. Question

You use a built-in tracking service to track specific workflow parameters.

You need to check whether the workflow parameters have been stored in the tracking database.

What should you do? (Each correct answer presents part of a solution. Choose two.)

A. Display the contents of the WorkflowInstance table of the tracking database.

B. Include the SqlTrackingQuery class in a code segment to retrieve tracked workflows and SqlTrackingWorkflowInstance class to inspect them.

C. Use the ActivityTrackingLocation class to determine if the value has been set to a database.

D. Display the contents of the TrackingDataItem table of the tracking database.

Answer: B AND D

9. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5. You use the state machine workflow in the application.

You plan to implement a mechanism that allows a host application to query a state machine workflow instance that is currently executing.

You write the following code segment. (Line numbers are included for reference only.)

```
01 WorkflowRuntime runtime = new WorkflowRuntime();
```

```
02 WorkflowInstance instance =
```

```
03 ?runtime.CreateWorkflow(typeof(Workflow1));
```

```
04 instance.Start();
```

```
05
```

You need to identify the current state of the workflow.

Which code segment should you insert at line 05?

A. string currentstate =

```
?instance.GetWorkflowDefinition().ToString();
```

B. string currentstate =

```
?instance.GetWorkflowDefinition().ExecutionStatus.ToString();
```

C. StateMachineWorkflowInstance smwi =

```
?new StateMachineWorkflowInstance(runtime, instance.InstanceId);
```

```
string currentstate = smwi.StateHistory[0];
```

D. StateMachineWorkflowInstance smwi =

```
?new StateMachineWorkflowInstance(runtime, instance.InstanceId);
```

```
string currentstate = smwi.CurrentStateName;
```

Answer: D

10. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5. You use the state machine workflow in the application.

You plan to implement a mechanism that allows a host application to query a state machine workflow instance that is currently executing.

You write the following code segment. (Line numbers are included for reference only.)

```
01 Dim runtime As New WorkflowRuntime()
```

```
02 Dim instance As WorkflowInstance = _
```

```
03 ?runtime.CreateWorkflow(GetType(Workflow1))
```

```
04 instance.Start()
```

```
05
```

You need to identify the current state of the workflow.

Which code segment should you insert at line 05?

A. Dim currentstate As String = instance.GetWorkflowDefinition().ToString

B. Dim currentstate As String = _

```
?instance.GetWorkflowDefinition().ExecutionStatus.ToString
```

C. Dim smwi As New StateMachineWorkflowInstance(runtime, _

```
?instance.InstanceId)
```

```
Dim currentstate As String = smwi.StateHistory(0)
```

```
D. Dim smwi As New StateMachineWorkflowInstance(runtime, _  
?instance.InstanceId)  
Dim currentstate As String = smwi.CurrentStateName
```

Answer: D

11. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5. The application contains a state workflow.

You write the following code segment.

```
WorkflowRuntime runtime = new WorkflowRuntime();  
WorkflowInstance instance = runtime.CreateWorkflow(  
?typeof(DynamicUpdateWorkflow));  
instance.Start();  
StateMachineWorkflowInstance smwi =  
?new StateMachineWorkflowInstance(runtime,  
?instance.InstanceId);
```

A dependency property named Status is defined in this workflow.

The value of a variable named amount is used to set the state of the workflow.

You need to ensure that the host application changes the state of the workflow on the basis of the value of the amount variable.

What are the two possible code segments that you can use to achieve this goal? (Each correct answer presents a complete solution. Choose two.)

A. if (amount >= 1000)

```
?smwi.SetState("HighValueState");  
else
```

```
?smwi.SetState("LowValueState");
```

B. if (amount >= 1000)

```
?smwi.StateMachineWorkflow.SetValue  
?(DynamicUpdateWorkflow.StatusProperty, "HighValueState")  
else
```

```
?smwi.StateMachineWorkflow.SetValue
```

```
?(DynamicUpdateWorkflow.StatusProperty, "LowValueState");
```

C. if (amount >= 1000)

```
?instance.GetWorkflowDefinition().SetValue  
?(DynamicUpdateWorkflow.StatusProperty, "HighValueState");  
else
```

```
?instance.GetWorkflowDefinition().SetValue
?(DynamicUpdateWorkflow.StatusProperty,"LowValueState");
D. if (amount >= 1000)
{
??StateActivity high = (StateActivity)
???smwi.StateMachineWorkflow.Activities["HighValueState"];
??smwi.SetState(high);
}
else
{
??StateActivity low = (StateActivity)
???smwi.StateMachineWorkflow.Activities["LowValueState"];
??smwi.SetState(low);
}
```

Answer: A AND D

12. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5. The application contains a state workflow.

You write the following code segment.

```
Dim amount As Integer = 10
Dim runtime As New WorkflowRuntime()
Dim instance As WorkflowInstance = _
?runtime.CreateWorkflow(GetType(DynamicUpdateWorkflow))
instance.Start()
Dim smwi As New StateMachineWorkflowInstance(runtime, _
?instance.InstanceId)
```

A dependency property named Status is defined in this workflow.

The value of a variable named amount is used to set the state of the workflow.

You need to ensure that the host application changes the state of the workflow on the basis of the value of the amount variable.

What are the two possible code segments that you can use to achieve this goal? (Each correct answer presents a complete solution. Choose two.)

A. If amount >= 1000 Then

```
??smwi.SetState("HighValueState")
```

Else

```
??smwi.SetState("LowValueState")
End If
B. If amount >= 1000 Then
??smwi.StateMachineWorkflow.SetValue _
???(DynamicUpdateWorkflow.StatusProperty, "HighValueState")
Else
??smwi.StateMachineWorkflow.SetValue _
???(DynamicUpdateWorkflow.StatusProperty, "LowValueState")
End If
C. If amount >= 1000 Then
??instance.GetWorkflowDefinition().SetValue
???(DynamicUpdateWorkflow.StatusProperty, "HighValueState")
Else
??instance.GetWorkflowDefinition().SetValue
???(DynamicUpdateWorkflow.StatusProperty, "LowValueState")
End If
D. If amount >= 1000 Then
??Dim high As StateActivity = _
???(CType(smwi.StateMachineWorkflow.Activities("HighValueState"), _
???)StateActivity)
??smwi.SetState(high)
Else
??Dim low As StateActivity = _
???(CType(smwi.StateMachineWorkflow.Activities("LowValueState"), _
???)StateActivity)
??smwi.SetState(low)
End If
```

Answer: A AND D

13. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5.

The application uses a markup-only workflow.

The workflow will also require the use of a code-beside file.

The following code fragment is implemented in XAML.

```
<SequentialWorkflowActivity
```

```
x:Class="ProcessNewCustomer" Name="ProcessCustomer" xmlns=
```

```
"http://schemas.microsoft.com/winfx/2006/xaml/workflow"  
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml">  
</SequentialWorkflowActivity>
```

You need to create a class declaration to implement the custom code.

Which code segment should you use?

A. public partial class ProcessNewCustomer

```
? : SequentialWorkflowActivity
```

```
{  
??// Class implementation code appears here.  
}
```

B. public class ProcessNewCustomer

```
? : SequentialWorkflowActivity
```

```
{  
??// Class implementation code appears here.  
}
```

C. public class ProcessNewCustomerCode

```
? : ProcessNewCustomer
```

```
{  
??// Class implementation code appears here.  
}
```

D. public partial class ProcessCustomer

```
? : SequentialWorkflowActivity
```

```
{  
??// Class implementation code appears here.  
}
```

Answer: A

14. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5.

The application uses a markup-only workflow.

The workflow will also require the use of a code-beside file.

The following code fragment is implemented in XAML.

```
<SequentialWorkflowActivity  
x:Class="ProcessNewCustomer" Name="ProcessCustomer" xmlns=  
"http://schemas.microsoft.com/winfx/2006/xaml/workflow"  
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml">
```

</SequentialWorkflowActivity>

You need to create a class declaration to implement the custom code.

Which code segment should you use?

A. Partial Public Class ProcessNewCustomer

??Inherits SequentialWorkflowActivity

??' Class implementation code appears here.

End Class

B. Public Class ProcessNewCustomer

??Inherits SequentialWorkflowActivity

??' Class implementation code appears here.

End Class

C. Public Class ProcessNewCustomerCode

??Inherits ProcessNewCustomer

??' Class implementation code appears here.

End Class

D. Partial Public Class ProcessCustomer

??Inherits SequentialWorkflowActivity

??' Class implementation code appears here.

End Class

Answer: A

15. Question

You create a workflow host application by using Microsoft .NET Framework 3.5. You use Windows Workflow Foundation to create the application.

You need to configure the workflow runtime to ensure that all the workflow instances run asynchronously.

Which code segment should you use?

A. WorkflowRuntime runtime = new WorkflowRuntime();

runtime.StartRuntime();

WorkflowInstance instance =

?runtime.CreateWorkflow(typeof(CustomerWorkflow));

instance.Start();

B. WorkflowRuntime runtime = new WorkflowRuntime();

runtime.StartRuntime();

ManualWorkflowSchedulerService scheduler =

?runtime.GetService<ManualWorkflowSchedulerService>();

WorkflowInstance instance =

```
?runtime.CreateWorkflow(typeof(CustomerWorkflow));
scheduler.RunWorkflow(instance.InstanceId);
C. WorkflowRuntime runtime = new WorkflowRuntime();
ManualWorkflowSchedulerService scheduler =
?new ManualWorkflowSchedulerService();
runtime.AddService(scheduler);
runtime.StartRuntime();
WorkflowInstance instance =
?runtime.CreateWorkflow(typeof(CustomerWorkflow));
instance.Start();
D. WorkflowRuntime runtime = new WorkflowRuntime();
runtime.StartRuntime();
DefaultWorkflowSchedulerService scheduler =
?new DefaultWorkflowSchedulerService();
runtime.AddService(scheduler);
WorkflowInstance instance =
?runtime.CreateWorkflow(typeof(CustomerWorkflow));
instance.Start();
```

Answer: A

16. Question

You create a workflow host application by using Microsoft .NET Framework 3.5. You use Windows Workflow Foundation to create the application.

You need to configure the workflow runtime to ensure that all the workflow instances run asynchronously.

Which code segment should you use?

```
A. Dim runtime As New WorkflowRuntime()
runtime.StartRuntime()
Dim instance As WorkflowInstance = _
?runtime.CreateWorkflow(GetType(CustomerWorkflow))
instance.Start()
B. Dim runtime As New WorkflowRuntime()
runtime.StartRuntime()
Dim scheduler As ManualWorkflowSchedulerService = _
?runtime.GetService(Of ManualWorkflowSchedulerService)()
Dim instance As WorkflowInstance = _
?runtime.CreateWorkflow(GetType(CustomerWorkflow))
```

```
scheduler.RunWorkflow(instance.InstanceId)
C. Dim runtime As New WorkflowRuntime()
Dim scheduler As New ManualWorkflowSchedulerService()
runtime.AddService(scheduler)
runtime.StartRuntime()
Dim instance As WorkflowInstance = _
?runtime.CreateWorkflow(GetType(CustomerWorkflow))
instance.Start()
D. Dim runtime As New WorkflowRuntime()
runtime.StartRuntime()
Dim scheduler As New DefaultWorkflowSchedulerService()
runtime.AddService(scheduler)
Dim instance As WorkflowInstance = _
?runtime.CreateWorkflow(GetType(CustomerWorkflow))
instance.Start()
```

Answer: A

17. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5.

A Windows Forms application functions as the workflow host by using the DefaultWorkflowSchedulerService.

You create a WorkflowRuntime instance in the Load event of the forms. You also subscribe to the WorkflowCompleted event.

You need to ensure that the application displays the message in the Label control named lblStatus when the WorkflowCompleted event is raised.

Which code segment should you use?

```
A. private void UpdateInstances(Guid id) {
??if (this.InvokeRequired) {
????lblStatus.Text = id + " completed";
??}
}
B. private void UpdateInstances(Guid id) {
??if (!this.InvokeRequired) {
????lblStatus.Text = id + " completed";
??}
}
```

```
C. delegate void UpdateInstancesDelegate(Guid id);
private void UpdateInstances(Guid id) {
    ??if (this.InvokeRequired) {
        ???this.Invoke(
            ?????new UpdateInstancesDelegate(UpdateInstances),
            ?????new object[] { id });
    ??} else {
        ????lblStatus.Text = id + " completed";
        ??}
    }
```

```
D. delegate void UpdateInstancesDelegate(Guid id);
private void UpdateInstances(Guid id) {
    ??if (!this.InvokeRequired) {
        ???this.Invoke(
            ?????new UpdateInstancesDelegate(UpdateInstances),
            ?????new object[] { id });
    ??} else {
        ????lblStatus.Text = id + " completed";
        ??}
    }
```

Answer: C

18. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5.

A Windows Forms application functions as the workflow host by using the DefaultWorkflowSchedulerService.

You create a WorkflowRuntime instance in the Load event of the forms. You also subscribe to the WorkflowCompleted event.

You need to ensure that the application displays the message in the Label control named lblStatus when the WorkflowCompleted event is raised.

Which code segment should you use?

A. Private Sub UpdateInstances(ByVal id As Guid)

??If Me.InvokeRequired Then

?????lblStatus.Text = id.ToString & " completed"

??End If

End Sub

```
B. Private Sub UpdateInstances(ByVal id As Guid)
??If (Not Me.InvokeRequired) Then
????lblStatus.Text = id.ToString & " completed"
??End If
End Sub

C. Private Delegate Sub UpdateInstancesDelegate(ByVal id As Guid)
Private Sub UpdateInstances(ByVal id As Guid)
??If Me.InvokeRequired Then
????Me.Invoke(New _
?????UpdateInstancesDelegate(AddressOf UpdateInstances), _
?????New Object() {id})
??Else
????lblStatus.Text = id.ToString & " completed"
??End If
End Sub

D. Private Delegate Sub UpdateInstancesDelegate(ByVal id As Guid)
Private Sub UpdateInstances(ByVal id As Guid)
??If Not Me.InvokeRequired Then
????Me.Invoke(New _
?????UpdateInstancesDelegate(AddressOf UpdateInstances), _
?????New Object() {id})
??Else
????lblStatus.Text = id.ToString & " completed"
??End If
End Sub
```

Answer: C

19. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5. The application uses a sequential workflow.

The host application creates a workflow instance and stores it in a variable named instance. When the workflow is executed, a business requirement requires the workflow execution to pause for a few minutes.

The host uses the following code segment.

```
WorkflowRuntime runtime = new WorkflowRuntime();
WorkflowInstance instance =
runtime.CreateWorkflow( typeof(Workflow1));
```

```
instance.Start();
```

You need to ensure that the following requirements are met:

The workflow execution is temporarily paused. The workflow state is preserved in memory.

Which line of code should you use?

A. instance.Unload();

B. instance.TryUnload();

C. instance.Suspend(null);

D. instance.Terminate(null);

Answer: C

20. Question

You create a Windows Workflow Foundation application by using Microsoft .NET Framework 3.5. The application uses a sequential workflow.

The host application creates a workflow instance and stores it in a variable named instance. When the workflow is executed, a business requirement requires the workflow execution to pause for a few minutes.

The host uses the following code segment.

```
Dim runtime As New WorkflowRuntime()
```

```
Dim instance As WorkflowInstance = _
```

```
?runtime.CreateWorkflow(GetType(MyWorkflow))
```

```
instance.Start()
```

You need to ensure that the following requirements are met:

The workflow execution is temporarily paused. The workflow state is preserved in memory.

Which line of code should you use?

A. instance.Unload()

B. instance.TryUnload()

C. instance.Suspend(Nothing)

D. instance.Terminate(Nothing)

Answer: C



Contact Test4pass

We are proud of our high-quality customer service, which serves you around the clock 24/7.

To get your problem resolved instantly, live support

Read Our Frequently Asked Questions (FAQs)

We have gathered the most frequently asked questions for you. Please read our list of FAQs.

Contact us by Live Messenger

Sales: [Test4pass\(at\)hotmail.com](mailto:Test4pass(at)hotmail.com)

You can reach us at any of the email addresses listed below

Please allow up to 24 hours for us to respond

- MSN: Test4pass@hotmail.com