

**Exam : Microsoft 70-552(C++)**

**Title : UPGRADE:MCAD Skills to  
MCPD Wdws Dvlpr by  
Using MS .NET Fmwk**

**Version : Demo**



## Top 3 Customers in Test4pass - Best IT certifications Team



Abbigail, who is proficient in Microsoft technology. After read our Study guides of Microsoft , She think test4pass is the best for IT candidates.

is the best for IT candidates.



Ramsden, who was majored in Manager IT technologys. He has many years of education experience. With his help, many of his candidates have won the certificate. he said:

test4pass' materials are the real one!



The IT experts of American company are training with test4pass braindumps, the manager of the company said: that will help them a lot

by using test4pass.

### HOT Certifications On Test4pass

#### Cisco Certifications

[CCNA](#) [CCDA](#) [CCNP](#) [CCDP](#) [CCVP](#) [CCSP](#) [CCIP](#) [CCIE](#) [CCDE](#) [Data Center](#) [Sales Expert](#)

#### Microsoft Certifications

[MCP](#) [MCSE](#) [MCITP](#) [MCTS](#) [MCSE2003](#) [MCPD](#) [MCSA.NET](#) [MCDST](#) [TS](#) [Exchange Server2007](#)  
[MCSE2003 Security](#) [MCSE2003 Messaging](#) [Microsoft Business Solutions](#)

#### IBM Certifications

[Certified Administrator](#) [Certified Systems Expert](#) [Solutions Expert](#) [System Administrator](#)  
[DB2](#) [Certified Advanced Technical Expert](#) [Certified Advanced System Administrator](#)  
[Lotus Certification](#) [WebSphere Cognos 8 BI](#) [Certified Associate Developer](#) [Tivoli Software](#)

#### CompTIA Certifications

[A+](#) [CDIA+](#) [CTT+](#) [e-Biz+](#) [CompTIA HTI+](#) [i-NET+](#) [Linux+](#) [Network+](#) [Project+](#) [RFID+](#) [Security+](#)  
[Server+](#) [PDI+](#) [Convergence+](#)

1. You are developing a utility screen for a new client application. The utility screen displays a thermometer that conveys the current status of processes being carried out by the application. You need to draw a rectangle on the screen to serve as the background of the thermometer as shown in the exhibit. The rectangle must be filled with gradient shading. (Click the Exhibit button.) Which code segment should you choose?



- A. `Rectangle^ rectangle = gnew Rectangle(10, 10, 450, 25); LinearGradientBrush^ rectangleBrush = gnew LinearGradientBrush(rectangle, Color::AliceBlue, Color::CornflowerBlue, LinearGradientMode::ForwardDiagonal); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->DrawRectangle(rectanglePen, rectangle);`
- B. `Rectangle^ rectangle = gnew Rectangle(10, 10, 450, 25); LinearGradientBrush^ rectangleBrush = gnew LinearGradientBrush(rectangle, Color::AliceBlue, Color::CornflowerBlue, LinearGradientMode::ForwardDiagonal); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->FillRectangle(rectangleBrush, rectangle);`
- C. `RectangleF^ rectangle = gnew RectangleF(10f, 10f, 450f, 25f); array<Point^>^ points = gnew array<Point^>^ {gnew Point(0, 0), gnew Point(110, 145)}; LinearGradientBrush^ rectangleBrush = gnew LinearGradientBrush(rectangle, Color::AliceBlue, Color::CornflowerBlue, LinearGradientMode::ForwardDiagonal); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->DrawPolygon(rectanglePen, points);`
- D. `RectangleF^ rectangle = gnew RectangleF(10f, 10f, 450f, 25f); SolidBrush^ rectangleBrush = gnew SolidBrush(Color::AliceBlue); Pen^ rectanglePen = gnew Pen(rectangleBrush); Graphics^ g = this->CreateGraphics(); g->DrawRectangle(rectangleBrush, rectangle);`

**Answer: B**

2. You create an application to send a message by e-mail. An SMTP server is available on the local subnet. The SMTP server is named smtp.contoso.com. To test the application, you use a source address, me@contoso.com, and a target address, you@contoso.com. You need to transmit the e-mail message. Which code segment should you use?

- A. `MailAddress addrFrom("me@contoso.com", "Me");MailAddress addrTo("you@contoso.com", "You");MailMessage message(%addrFrom, %addrTo);message.Subject = "Greetings!";message.Body = "Test";message.Dispose();`
- B. `String^ strSmtpClient = "smtp.contoso.com";String^ strFrom = "me@contoso.com";String^ strTo = "you@contoso.com";String^ strSubject = "Greetings!";String^ strBody = "Test";MailMessage msg(strFrom, strTo, strSubject, strSmtpClient);`

C. `MailAddress addrFrom("me@contoso.com");MailAddress addrTo("you@contoso.com");MailMessage message(%addrFrom, %addrTo);message.Subject = "Greetings!";message.Body = "Test";SmtpClient client("smtp.contoso.com");client.Send(%message);`

D. `MailAddress^ addrFrom = gnew MailAddress("me@contoso.com", "Me");MailAddress^ addrTo = gnew MailAddress("you@contoso.com", "You");MailMessage^ message = gnew MailMessage(addrFrom, addrTo);message->Subject = "Greetings!";message->Body = "Test";SocketInformation info;Socket^ client = gnew Socket(info);System::Text::ASCIIEncoding^ enc = gnew System::Text::ASCIIEncoding();array<unsigned char>^ msgBytes = enc->GetBytes(message->ToString());client->Send(msgBytes);`

**Answer: C**

3. You need to write a code segment that will add a string named `strConn` to the connection string section of the application configuration file. Which code segment should you use?

A. `System::Configuration::Configuration^ myConfig = ConfigurationManager::OpenExeConfiguration(ConfigurationUserLevel::None);myConfig->ConnectionStrings->ConnectionStrings->Add(gnew ConnectionStringSettings("ConnStr1", strConn));myConfig->Save();`

B. `System::Configuration::Configuration^ myConfig = ConfigurationManager::OpenExeConfiguration(ConfigurationUserLevel::None);myConfig->ConnectionStrings->ConnectionStrings->Add(gnew ConnectionStringSettings("ConnStr1", strConn));ConfigurationManager::RefreshSection("ConnectionStrings");`

C. `ConfigurationManager::ConnectionStrings::Add(gnew ConnectionStringSettings("ConnStr1", strConn));ConfigurationManager::RefreshSection("ConnectionStrings");`

D. `ConfigurationManager::ConnectionStrings::Add(gnew ConnectionStringSettings("ConnStr1", strConn));System::Configuration::Configuration^ myConfig = ConfigurationManager::OpenExeConfiguration(ConfigurationUserLevel::None);myConfig->Save();`

**Answer: A**

4. You are using the Microsoft Visual Studio 2005 IDE to examine the output of a method that returns a string. You assign the output of the method to a string variable named `fName`.

You need to write a code segment that prints the following on a single line

The message: "Test Failed: "

The value of `fName` if the value of `fName` does not equal "John"

You also need to ensure that the code segment simultaneously facilitates uninterrupted execution of the application. Which code segment should you use?

A. `Debug::Assert(fName == "John", "Test Failed: ", fName);`

B. `Debug::WriteLineIf(fName != "John", fName, "Test Failed");`

- C. if (fName != "John") { Debug::Print("Test Failed: "); Debug::Print(fName);}
- D. if (fName != "John") { Debug::WriteLine("Test Failed: "); Debug::WriteLine(fName);}

**Answer: B**

5. You are developing an application that will deploy by using ClickOnce. You need to test if the application executes properly. You need to write a method that returns the object, which prompts the user to install a ClickOnce application. Which code segment should you use?

- A. return ApplicationSecurityManager::ApplicationTrustManager;
- B. return AppDomain::CurrentDomain::ApplicationTrust;
- C. return gnew HostSecurityManager();
- D. return SecurityManager::PolicyHierarchy();

**Answer: A**

6. You are developing a method to hash data with the Secure Hash Algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using SHA1. You also need to place the result into a byte array named hash. Which code segment should you use?

- A. SHA1 ^sha = gnew SHA1CryptoServiceProvider();array<Byte>^hash = nullptr;sha->TransformBlock(message, 0, message->Length, hash, 0);
- B. SHA1 ^sha = gnew SHA1CryptoServiceProvider();array<Byte>^hash = BitConverter::GetBytes(sha->GetHashCode());
- C. SHA1 ^sha = gnew SHA1CryptoServiceProvider();array<Byte>^hash = sha->ComputeHash(message);
- D. SHA1 ^sha = gnew SHA1CryptoServiceProvider();sha->GetHashCode();array<Byte>^hash = sha->Hash;

**Answer: C**

7. You create a DirectorySecurity object for the working directory. You need to identify the user accounts and groups that have read and write permissions. Which method should you use on the DirectorySecurity object?

- A. the GetAuditRules method
- B. the GetAccessRules method
- C. the AccessRuleFactory method
- D. the AuditRuleFactory method

**Answer: B**

8. You are creating an assembly named Assembly1. Assembly1 contains a public method. The global cache contains a second assembly named Assembly2. You must ensure that the public method is only called from Assembly2. Which permission class should you use?

- A. GaclIdentityPermission

- B. PublisherIdentityPermission
- C. DataProtectionPermission
- D. StrongNameIdentityPermission

**Answer: D**

9. You are changing the security settings of a file named MyData.xml. You need to preserve the existing inherited access rules. You also need to prevent the access rules from inheriting changes in the future. Which code segment should you use?

- A. `FileSecurity^ security = gnew FileSecurity("mydata.xml",AccessControlSections::All);security->SetAccessRuleProtection(true, true);File::SetAccessControl("mydata.xml", security);`
- B. `FileSecurity^ security = gnew FileSecurity();security->SetAccessRuleProtection(true, true);File::SetAccessControl("mydata.xml", security);`
- C. `FileSecurity^ security = File::GetAccessControl("mydata.xml");security->SetAccessRuleProtection(true, true);`
- D. `FileSecurity^ security = File::GetAccessControl("mydata.xml");security->SetAuditRuleProtection(true, true);File::SetAccessControl("mydata.xml", security);`

**Answer: A**

10. You are writing code for user authentication and authorization. The username, password, and roles are stored in your application data store. You need to establish a user security context that will be used for authorization checks such as `IsInRole`. You write the following code segment to authorize the user.

```
if (!TestPassword(userName, password))
    throw new Exception("could not authenticate user");
String[] userRolesArray = LookupUserRoles(userName);
```

You need to complete this code so that it establishes the user security context. Which code segment should you use?

- A. `GenericIdentity ident = new GenericIdentity(userName);GenericPrincipal currentUser = new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;`
- B. `WindowsIdentity ident = new WindowsIdentity(userName);WindowsPrincipal currentUser = new WindowsPrincipal(ident);Thread.CurrentPrincipal = currentUser;`
- C. `NTAccount userNTName = new NTAccount(userName);GenericIdentity ident = new GenericIdentity(userNTName.Value);GenericPrincipal currentUser= new GenericPrincipal(ident, userRolesArray);Thread.CurrentPrincipal = currentUser;`
- D. `IntPtr token = IntPtr.Zero;token = LogonUserUsingInterop(userName, encryptedPassword);WindowsImpersonationContext ctx = WindowsIdentity.Impersonate(token);`

**Answer: A**

11. You are developing a server application that will transmit sensitive information on a network. You create an X509Certificate object named certificate and a TcpClient object named client. You need to create an SslStream to communicate by using the Transport Layer Security 1.0 protocol. Which code segment should you use?

- A. `SslStream^ ssl = gnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::None, true);`
- B. `SslStream ^ssl = gnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Ssl3, true);`
- C. `SslStream ^ssl = gnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Ssl2, true);`
- D. `SslStream ^ssl = gnew SslStream(Client->GetStream());ssl->AuthenticateAsServer(certificate, false, SslProtocols::Tls, true);`

**Answer: D**

12. You are developing an auditing application to display the trusted ClickOnce applications that are installed on a computer. You need the auditing application to display the origin of each trusted application. Which code segment should you use?

- A. `ApplicationTrustCollection^ trusts;trusts= ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;i<trusts->Count;i++){ApplicationTrust^ trust = trusts[i];System::Console::WriteLine(trust->ToString());}`
- B. `ApplicationTrustCollection^ trusts;trusts = ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;i<trusts->Count;i++){ApplicationTrust^ trust = trusts[i];System::Console::WriteLine(trust->ExtraInfo->ToString());}`
- C. `ApplicationTrustCollection^ trusts;trusts = ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;i<trusts->Count;i++){ApplicationTrust^ trust = trusts[i];System::Console::WriteLine(trust->ApplicationIdentity->FullName);}`
- D. `ApplicationTrustCollection^ trusts;trusts = ApplicationSecurityManager::UserApplicationTrusts;for(int i=0;i<trusts->Count;i++){Object^ trust = trusts[i];System::Console::WriteLine(trust->ToString());}`

**Answer: C**

13. You are developing a method to call a COM component. You need to use declarative security to explicitly request the runtime to perform a full stack walk. You must ensure that all callers have the required level of trust for COM interop before the callers execute your method. Which attribute should you place on the method?

- A. `[SecurityPermission( SecurityAction::Demand, Flags=SecurityPermissionFlag::UnmanagedCode)]`
- B. `[SecurityPermission( SecurityAction::LinkDemand, Flags=SecurityPermissionFlag::UnmanagedCode)]`

- C. [SecurityPermission( SecurityAction::Assert, Flags = SecurityPermissionFlag::UnmanagedCode)]
- D. [SecurityPermission( SecurityAction::Deny, Flags = SecurityPermissionFlag::UnmanagedCode)]

**Answer: A**

14. You are developing a method to hash data for later verification by using the MD5 algorithm. The data is passed to your method as a byte array named message. You need to compute the hash of the incoming parameter by using MD5. You also need to place the result into a byte array. Which code segment should you use?

- A. HashAlgorithm ^algo = HashAlgorithm::Create("MD5");hash = algo->ComputeHash(message);
- B. HashAlgorithm ^algo = HashAlgorithm::Create("MD5");hash = BitConverter::GetBytes(algo->GetHashCode());
- C. HashAlgorithm ^algo;algo = HashAlgorithm::Create(message->ToString());hash = algo->Hash;
- D. HashAlgorithm ^algo = HashAlgorithm::Create("MD5");hash = nullptr;algo->TransformBlock(message, 0, message->Length, hash, 0);

**Answer: A**

15. You are developing an application that will use custom authentication and role-based security. You need to write a code segment to make the runtime assign an unauthenticated principal object to each running thread. Which code segment should you use?

- A. AppDomain^ domain = AppDomain::CurrentDomain;domain->SetPrincipalPolicy(PrincipalPolicy::WindowsPrincipal);
- B. AppDomain^ domain = AppDomain::CurrentDomain;domain->SetThreadPrincipal(gcnew WindowsPrincipal(nullptr));
- C. AppDomain^ domain = AppDomain::CurrentDomain;domain->SetAppDomainPolicy(PolicyLevel::CreateAppDomainLevel());
- D. AppDomain^ domain = AppDomain::CurrentDomain;domain->SetPrincipalPolicy(PrincipalPolicy::UnauthenticatedPrincipal);

**Answer: D**

16. You are developing an application that runs by using the credentials of the end user. Only users who are members of the Administrator group get permission to run the application. You write the following security code to protect sensitive data within the application.

```
bool isAdmin = false;
WindowsBuiltInRole role = WindowsBuiltInRole.Administrator;
...
if (!isAdmin)
```

```
throw new Exception("User not permitted");
```

You need to add a code segment to this security code to ensure that the application throws an exception if a user is not a member of the Administrator group. Which code segment should you use?

- A. `WindowsPrincipal currentUser = (WindowsPrincipal)Thread.CurrentPrincipal;isAdmin = currentUser.IsInRole(role);`
- B. `WindowsIdentity currentUser = WindowsIdentity.GetCurrent();foreach (IdentityReference grp in currentUser.Groups) { NTAccount grpAccount = ((NTAccount)grp.Translate(typeof(NTAccount))); isAdmin = grp.Value.Equals(role); if (isAdmin) break;}`
- C. `GenericPrincipal currentUser = (GenericPrincipal) Thread.CurrentPrincipal;isAdmin = currentUser.IsInRole(role.ToString());`
- D. `WindowsIdentity currentUser = (WindowsIdentity)Thread.CurrentPrincipal.Identity;isAdmin = currentUser.Name.EndsWith("Administrator");`

**Answer: A**

17. You need to create a method to clear a Queue named q. Which code segment should you use?

- A. `for each (Object^ e in q) { q.Dequeue();}`
- B. `for each (Object^ e in q) { q.Enqueue(0);}`
- C. `q.Clear();`
- D. `q.Dequeue();`

**Answer: C**

18. You are creating a class that uses unmanaged resources. This class maintains references to managed resources on other objects. You need to ensure that users of this class can explicitly release resources when the class instance ceases to be needed. Which three actions should you perform? (Each correct answer presents part of the solution. Choose three.)

- A. Define the class such that it inherits from the WeakReference class.
- B. Define the class such that it implements the IDisposable interface.
- C. Create a class destructor that calls methods on other objects to release the managed resources.
- D. Create a class destructor that releases the unmanaged resources.
- E. Create a Dispose method that calls System.GC.Collect to force garbage collection.
- F. Create a Dispose method that releases unmanaged resources and calls methods on other objects to release the managed resources.

**Answer: BDF**

19. You are writing a custom dictionary. The custom-dictionary class is named MyDictionary. You need to ensure that the dictionary is type safe. Which code segment should you use?

- A. `public ref class MyDictionary : public Dictionary<String^, String^>{}`

- B. public ref class MyDictionary : public Hashtable{};
- C. public ref class MyDictionary : public IDictionary{};
- D. public ref class MyDictionary{};Dictionary<String^, String^> t = gnew Dictionary<String^, String^>();MyDictionary dictionary = (MyDictionary)t;

**Answer:** A

20. You are creating an undo buffer that stores data modifications. You need to ensure that the undo functionality undoes the most recent data modifications first. You also need to ensure that the undo buffer permits the storage of strings only. Which code segment should you use?

- A. Stack<String^> undoBuffer = gnew Stack<String^>();
- B. Stack undoBuffer = gnew Stack();
- C. Queue<String^> undoBuffer = gnew Queue<String^>();
- D. Queue undoBuffer = gnew Queue();

**Answer:** A



## Contact Test4pass

We are proud of our high-quality customer service, which serves you around the clock 24/7.

**To get your problem resolved instantly, live support**

**Read Our Frequently Asked Questions (FAQs)**

We have gathered the most frequently asked questions for you. Please read our list of FAQs.

**Contact us by Live Messenger**

Sales: [Test4pass\(at\)hotmail.com](mailto:Test4pass(at)hotmail.com)

**You can reach us at any of the email addresses listed below**

Please allow up to 24 hours for us to respond

- MSN: Test4pass@hotmail.com